



Wall Mounted Solar Battery

RZE-25200LI-WS



Safe & Reliable



6000+ cycles @%80 DOD
and 5 years warranty.



Modular design
without mounting bracket.



One key on/off,
redundancy protection.



Live communication, and compatible with most leading LV inverters.

GOODWE

Deye 德業

Growatt

victron energy
BLUE POWER

SMA

Volttronk Power

SUNGROW

SRNE

EPEVER



Rizon Technologies

75-71, Shelton Street, Covent Garden, London, WC2H9JQ, UNITED KINGDOM

+442081871184

info@rizontechnologies.com



RZE-25200LI-WS

Battery Module	RZE-25200LI-WS
Battery category	LiFePO4
Rated energy (kWh) (25 °C, 0.5C)	5.12
Rated voltage (V)	25.6
Rated capacity (Ah)	200
Max. charging and discharging current (A)	200
Charging and discharging current (A)	100 (Recommended)
Dimension (W*D*H, mm)	360*(540+32)*158
Weight (Kg)	45
Operating voltage (V)	22.4V-28.8V
Working temperature	0°C~45°C, Recommend 15°C~30°C
Communication	CAN/RS485/WIFI
Degree of protection	IP20

■ Products specifications described herein are subject to change without prior notification.