



VRLA BATTERY FOR ENERGY STORAGE

RZE6-26S1

RZE6-26S1 VRLA battery uses AGM technology and high-purity raw materials. It is good floating back up and large current discharge performance makes it optimal and economical choice for UPS/EPS.

Main Applications

- ▶ UPS units
- ▶ Emergency power
- ▶ Starting generators
- ▶ EPS units


Benefits

- ▶ Standard Commercial according to EUROBAT Classification
- ▶ Maximum charge efficiency
- ▶ High gas recombination efficiency Low self-discharge rate Easy
- ▶ installation and handling Vertical or horizontal installation

Standards

- ▶ IEC 60896-21/22 JIS
- ▶ C8704-1/2
- ▶ EUROBAT guide

Dimensions





Technical Parameters

Battery Model		RZE6-26S1			
Design Life (years, 25°C)	10				
Capacity (Ah, 25°C)	20HR (1.3A, 1.75V)	10HR (2.42A, 1.75V)	5HR (4.701A, 1.75V)	1HR(16.37A, 1.70V)	
	26	24.2	23.5	16.37	
Dimensions (mm)	Length	Width	Height	Total Height	
	166	175	125	125	
Approx. Weight (kg)	8.0				
Reference Internal Resistance (mΩ)	8.8 (full charged @ 25°C)				
Maximum Discharge Current (A/5 Sec.)	390				
Self-Discharge (25°C)	≤ 3 % per month				
Charge Voltage (V/cell, 25°C)	Cycle use			Float use	
	2.45 (-3.5mV/°C/cell), max charge current: 7.8 A			2.27 (-3.5mV/°C/cell)	
Short Circuit Current (A)	780				

Discharge Data


Constant Current Discharge Data (25°C, A)

End Voltage (V/cell)	min					h						
	10	15	20	30	45	1	1.5	2	3	5	10	20
1.60	63.26	50.31	41.07	29.20	20.62	16.72	11.90	9.620	7.140	4.779	2.456	1.317
1.65	61.32	49.07	40.48	28.96	20.45	16.61	11.83	9.553	7.102	4.757	2.447	1.312
1.67	59.79	48.36	39.98	28.67	20.29	16.50	11.76	9.509	7.073	4.739	2.438	1.308
1.70	58.36	47.61	39.47	28.35	20.09	16.37	11.68	9.451	7.032	4.717	2.427	1.303
1.75	56.94	46.80	39.00	28.08	19.93	16.26	11.61	9.404	7.003	4.701	2.420	1.300
1.80	53.30	44.65	37.71	27.35	19.49	15.96	11.42	9.307	6.947	4.670	2.405	1.294


Constant Power Discharge Data (25°C, W/cell)

End Voltage (V/cell)	min					h						
	10	15	20	30	45	1	1.5	2	3	5	10	20
1.60	118.6	96.04	79.25	56.75	40.32	32.86	23.48	19.05	14.18	9.520	4.909	2.636
1.65	115.4	93.92	78.37	56.43	40.11	32.74	23.41	18.96	14.15	9.498	4.902	2.634
1.67	112.9	92.86	77.68	56.06	39.91	32.59	23.31	18.92	14.12	9.485	4.895	2.633
1.70	110.7	91.68	76.81	55.54	39.58	32.40	23.20	18.84	14.06	9.458	4.880	2.627
1.75	108.4	90.38	76.08	55.12	39.35	32.23	23.12	18.78	14.03	9.445	4.877	2.626
1.80	101.9	86.52	73.76	53.84	38.60	31.73	22.80	18.64	13.96	9.404	4.858	2.619


Performance Curve




Discharge voltage vs. discharge time



Charge capacity vs. charge time



Discharge capacity vs. temperature



Design life vs. temperature

⚠ Declaration: This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact Rizon Technologies for the latest information

■ Products specifications described herein are subject to change without prior notification.